



Fulflo® ProBond™ Filter Cartridges

■ Acrylic/Phenolic

Bonded Depth Series

A Patented Breakthrough in Resin Bonded Cartridge Design

Parker ProBond™ cartridges have a unique, proprietary* two-stage filtration design to maximize particle removal and service life in viscous fluid filtration applications. An outer, spiral, prefilter wrap increases cartridge strength and eliminates residual debris associated with conventional, machined, resin bonded cartridges.

ProBond filter cartridges are available in eight differentiated removal ratings from 2µm, 5µm, 10µm, 25µm, 50µm, 75µm, 125µm and 150µm pore sizes to meet a wide range of performance requirements.

Applications

- Paints
- Printing Inks
- Adhesives
- Resins
- Emulsions
- Chemical Coatings
- Organic Solvents
- Petroleum Products
- Process Water
- Oilfield Fluids
- Animal Oils
- Waxes
- Plasticizers



Features and Benefits

- Outer, spiral wrap collects large particles and agglomerates, while inner layers control particle removal at rated size.
- Outer wrap increases surface area and eliminates loose debris and contamination caused by machined products.
- Extra-long acrylic fibers provide added strength, resist breakage and migration common with competitive “short fiber” cartridges.
- Available with optimal single-open-end seals (222 o-ring with flat cap) in ABS or nylon.
- Phenolic resin impregnation strengthens cartridge for use with fluid viscosities up to 15,000 SSU (3200 cks).
- Withstands pressure surges up to 150 psid across cartridge (depending on fluid temperature).
- One-piece construction eliminates bypass concerns with multilength cartridges and eases change out.
- Silicone-free construction ensures no contamination to adversely affect adhesion properties of coatings.

Process Filtration Division



Bonded Depth Series

Specifications

Materials of Construction:

- Acrylic, long staple fiber; phenolic bonding resin

Type of Construction:

- Coreless, one-piece, rigid resin bonded fibrous matrix

Particle Removal Ratings:

- 2µm, 5µm, 10µm, 25µm, 50µm, 75µm, 125µm and 150µm

Dimensions, in (mm):

- Outside Diameter: 2-9/16 in (65)
- Inside Diameter: 1-1/8 in (28.6)
- Lengths: Nominal, 10, 20, 30 and 40 in lengths

End Adapters:

- None on double open end style
- ABS (Acrylonitrile Butadiene Styrene) for most applications.
- Nylon (NTC) for aromatic solvents.

Maximum Recommended

Operating Conditions:

- Flow Rate: 10 gpm per 10 in length (38 lpm per 254 mm length)
- Temperature: 250°F (121°C)
- Change Out ΔP: 50 psid (3.5 bar)
- Cartridge Pressure Resistance: 150 psid (10 bar) @ 70°F (21°C) 125 psid (8.6 bar) @ 100°F (38°C) 90 psid (6.2 bar) @ 150°F (65°C) 65 psid (4.5 bar) @ 180°F (82°C) 25 psid (1.7 bar) @ 250°F (121°C)

Environmental/Chemical Compatibility:

- Classified as a nonhazardous material
- Incinerable (8000 BTU/lb)
- Crushable and shreddable
- Certified silicone-free
- Suitable for weak acids and bases (pH 5-9)
- Unsuitable for oxidizing agents
- Not recommended for FDA applications

ProBond Length Factors

Length (in)	Length Factor
9	1.0
10	1.0
19	2.0
20	2.0
29	3.0
30	3.0
39	4.0
40	4.0

ProBond Flow Factors (psid/gpm @ 1cks)

Rating (µm)	Flow Factor
2	0.08
5	0.04
10	0.02
25	0.012
50	0.01
75	0.006
125	0.0013
150	0.0010

Flow Rate and Pressure Drop Formulae:

$$\text{Flow Rate (gpm)} = \frac{\text{Clean } \Delta P \times \text{Length Factor}}{\text{Viscosity} \times \text{Flow Factor}}$$

$$\text{Clean } \Delta P = \frac{\text{Flow Rate} \times \text{Viscosity} \times \text{Flow Factor}}{\text{Length Factor}}$$

Notes:

- Clean ΔP is PSI differential at start.
- Viscosity is centistokes. Use Conversion Tables for other units.
- Flow Factor is ΔP/GPM at 1 cks for 10 in (or single).
- Length Factors convert flow or ΔP from 10 in (single length) to required cartridge length.

Ordering Information

PRO	5	—	29
Cartridge Code	Micron Rating (µm)		Length (code) (in) (mm)
	2		(code) (in) (mm)
	5		9 9-3/4 248
	10		10 10 254
	25		19 19-1/2 495
	50		20 20 508
	75		29 29-1/4 743
	125		30 30 762
	150		39 39 961
			39 39 991
			40 40 1016

PRO = ProBond Series

X A	—	N
End Cap Configurations		Seal Material
Omit = Standard DOE (coreless)		Omit = DOE or XA
CXC = Extended Tinned Steel Core		N = Buna-N O-Ring
C = Tinned Steel Core		E = EPR O-Ring
NTC = Single Open End 222 O-ring/Flat Cap (Nylon)		S = Silicone O-Ring
OB = Std. Open End/Polypro Spring Closed End		V = Viton** O-Ring
TC = Single Open End 222 O-Ring/Flat Cap (ABS Plastic)		W = Poly Foam Gaskets
XA = Poly Extender		
XB = Ext. Core Open End/Polypro Spring Closed End		

Process Filtration Division

Parker Hannifin Corporation
 Process Filtration Division
 6640 Intech Boulevard
 Indianapolis, Indiana 46278
 Toll Free 1-888-C-FULFLO (238-5356)
 Telephone (317) 275-8300
 Fax (317) 275-8410
<http://www.parker.com>



* U.S. Patent No. 5,639,370

** A trademark of E. I. duPont de Nemours & Co.