



Balston Disposable Filter Units

Parker Hannifin Corporation, the leader in separation and filtration technologies, is pleased to present a brochure designed to help customers choose the best Balston disposable filter product for industrial, commercial, measurement and control applications.

Balston brand disposable filter units (DFU) consist of a microfibre filter cartridge permanently bonded into a sealed plastic holder with 125 psig pressure ratings, temperatures to 275°F, and available in low and high flow models. The economical DFU offers all of the advantages of microfibre filter cartridges for high efficiency liquid and gas filtration, combined with the economics and convenience of complete disposability.

Our years of experience in fitting products to individual applications has led to the creation of a variety of standard products that can be ordered off the shelf for general purpose filtration requirements or can be custom designed for all types of specialty applications.

If you do not see the specific configuration, size or material that you are looking for, our OEM engineering team will be happy to review your requirements and design product to your exact specifications.

If you have questions, or would like to place an order, please call 1-800-343-4048.

Ideal for the following gas filtration applications:

- Final filter for air logic devices
- Protection of pneumatic components
- Filtration of portable environmental sampling devices
- Filtration of samples to on-line analyzers
- Protection of Pneumatic temperature controls


Ideal for the following liquid filtration applications:

- Filtration of liquid with minimum holdup volume
- Filtration of liquid samples to analyzers

Additional applications in the following industries:

- Instrument & Controls
- HVAC
- Dental
- Automotive
- Food Packaging

General Purpose DFU - Low Flow Gas



Specifications


Max. Pressure at 110°F:	125 psig
Max. Temp. at 0 psig:	230°F (110°C)
Inlet / Outlet Ports:	1/4" Tube
Drain:	None
Housing Material of Construction:	Nylon
Internal Volume:	.01L

Ordering Information

9933-05-□ Box of 10
Available in Type Q and in the following grades: A, B, C, D. Also available with adsorbents 000, 101, 103, 107.

Model 9933-05

General Purpose DFU - Higher Flow



Specifications


Max. Pressure at 110°F:	125 psig
Max. Temp. at 0 psig:	230°F (110°C)
Inlet / Outlet Ports:	1/4" Tube
Drain:	None
Housing Material of Construction:	Nylon
Internal Volume:	.02L

Ordering Information

9933-11-□ Box of 10
Available in Type Q and in the following grades: A, B, C, D. Also available with adsorbents 000, 101, 103, 107.

Model 9933-11

General Purpose with Integral Barb Fittings



Specifications


Max. Pressure at 110°F:	125 psig
Max. Temp. at 0 psig:	230°F (110°C)
Inlet / Outlet Ports:	1st Tier: 1/4" Tube 2nd Tier: 3/8" Tube
Drain:	None
Material of Construction:	Nylon
Internal Volume:	.01L

Ordering Information

4433-05-□ Box of 10
Available in Type Q and in grades: A, B, C and D
Also available with adsorbents 000, 101, 103, 107.

Model 4433-05

General Purpose with Drain Port



Specifications


Max. Pressure at 110°F:	125 psig
Max. Temp. at 0 psig:	230°F (110°C)
Inlet / Outlet Ports:	1/4" Tube
Drain:	1/4" Tube
Housing Material of Construction:	Nylon
Internal Volume:	.02L

Ordering Information

8833-11-□ Box of 10
Available in Types Q and X and in the following grades: A, B, C, D, S. Also available with adsorbents 000, 101, 103, 107.

Model 8833-11

High Chemical Resistance - Low Flow




Specifications	
Max. Pressure at 110°F:	125 psig
Max. Temp. at 0 psig:	275°F (135°C)
Inlet / Outlet Ports:	1/4" Tube
Drain:	None
Housing Material of Construction:	PVDF
Internal Volume:	.01L

Ordering Information	
9922-05-□	Box of 10
Available in Type Q and in the following grades: A, B, C, D. Also available with adsorbents 000, 101, 103, 107.	

Model 9922-05

High Chemical Resistance DFU -Higher Flow




Specifications	
Max. Pressure at 110°F:	125 psig
Max. Temp. at 0 psig:	275°F (135°C)
Inlet / Outlet Ports:	1/4" Tube
Drain:	None
Housing Material of Construction:	PVDF
Internal Volume:	.02L

Ordering Information	
9922-11-□	Box of 10
Available in Types Q and in the following grades: A, B, C, D	

Model 9922-11

Oil Indicating DFU




Specifications	
Max. Pressure at 110°F:	125 psig
Max. Temp. at 0 psig:	230°F (110°C)
Inlet / Outlet Ports:	1/4" Tube
Drain:	None
Housing Material of Construction:	Nylon
Internal Volume:	.01L

Ordering Information	
9900-05-□	Box of 10
Available in Type K and in grade B.	

Model 9900-05

Large Capacity High Flow DFU




Specifications	
Max. Pressure at 110°F:	50 psig
Max. Temp. at 0 psig:	150°F
Inlet / Outlet Ports:	1/2" Tube
Drain:	None
Housing Material of Construction:	Nylon
Internal Volume:	.0138L

Ordering Information	
8800-12-□	Box of 1
Available in Types Q and X and in the following grades: A, B, C, D	

Model 8800-12

Large Capacity High Flow DFU Intake Filter



Specifications	
Max. Pressure at 110°F:	2 psig
Max. Temp. at 0 psig:	125°F
Inlet / Outlet Ports:	.032" OD
Drain:	None
Housing Material of Construction:	Polypropylene
Internal Volume:	0.033L

Ordering Information	
9953-11-□	Box of 10
Available in Types Q and X and in the following grades: A, B, C, D	

Model 9953-11

